



# CitySpirit – streetwise

### CitySpirit Cone LED BDS470 C

CitySpirit is a range of street-lighting luminaires designed to provide excellent, environmentally friendly lighting without compromising on architectural appearance. The distinctive designs are clearly linked yet allow modularity. To ensure perfect integration in the urban streetscape, the luminaire, mast and bracket of CitySpirit have been developed as one design. The range provides elegant and above all complete project solutions. Furthermore, transparent materials have been used to lighten the daytime appearance. CitySpirit incorporates several optical concepts, which address issues such as spacing, night preservation, visual comfort and light trespass. All CitySpirit indirect versions are retrofit luminaires, which can be equipped with conventional or LED light sources. In combination with different optical reflectors they deliver indirect high-quality warm white light. CitySpirit indirect LED has an upgradeable LED light engine, which ensures future-proof performance. Together with its constant light output and dimming functionality, the LED version ensures the highest operational efficiency. The range further comprises Cone, Torch, Street and Street Color models.

#### **Benefits**

- Perfect integration in the urban architecture, with luminaire, mast and bracket designed as an integrated concept
- Matches excellent urban lighting performance during darkness hours with outstanding aesthetics during the day
- Wide choice of masts, brackets, lanterns and optical elements offers complete, elegant solutions for every situation

#### **Features**

- High-quality high-power LED's with integrated LED driver
- Lifetime over 50,000 hours (70% lulmen maintenance) at Ta=25<SUP>o</SUP>C
- Robust design IP65 protection and IK09 impact resistance
- Choice of warm white (3000K) and neutral white (4000K)

# CitySpirit Cone LED BDS470 C

## Application

- Pathway lighting
- Landscape lighting
- Parks and gardens

#### **Specifications**

Туре	BDS470
Light source	22 x SMD LED-HP
Light color	Warm white, 3000 K (WW)
	Neutral white, 4000 K (NW)
Power consumption	System 30 W (typical)
Inrush current	20 A / 40 μs
Driver	220-240 V / 50-60 Hz
Optical element	Top reflector, indirect asymmetrical (TA IO)
	Top reflector, indirect bi-directional (TB-LED IO)
	Top reflector, indirect symmetrical (TS IO)
Optical cover	Transparent bowl/cover (TB)
Controls	Compatible with full line of Philips 1-10 V controllers

Options	Lumistep (pre-programmed dimming)
	1-10 V input (dimming via external control)
Material	Housing: high-pressure, die-cast aluminum, non-corrosive
	Pole mount: die-cast aluminum
	Bowl and skirt: polycarbonate, translucent UV-stabilized
	Top cover: ABS with heat shield
	Reflectors: anodized aluminum, brightened 99.99%
Color	Canopy: ultra dark grey, approx RAL 7043 (GR)
Installation	Flanged or embedded
Lifetime	50,000 hours (70% lumen maintenance)
Remarks	CRI 80
	Constant Light Output

#### Versions



CDS470 C 220-240V IO

#### **Product details**





# CitySpirit Cone LED BDS470 C

#### Product details

LED module





LED module

