GreenUp – BY200 **LED WelGlass**



GreenUp LED Welglass luminaire is designed to replace traditional WelGlass up to 70W with only 35% of the load for similar illumination. It is a perfect LED solution for outdoor application and industry of harsh condition like power plant, metal, and non hazardous area in chemical and petrochemical industry. Compared to conventional HID WelGlass, it improves reliability, comfort, while reducing energy and maintenance cost dramatically. GreenUp Welglass comes with 2 different mounting,

pipe and bracket, and comes with 2 beam, lambertian and batwing.





Basic Unit

intensity diagram



Bracket



Benefits

Energy savings up to 68% compared to HID systems

• Solid die-cast housing design with corrosion proof coating to ensures long fixture lifetime Extra protection against impact with optional

Application flexibility (pipe mounting and bracket

stainless steel wire guard

for wall/ceiling mounting)

Energy efficient


- Long lifetime
- Comfortable light with low glare ratings
- Unique flat design for various mounting
- Wide Beam, Narrow Beam & High Rack Optic Beam

Applications

Harsh Industry Application







BatWing



GreenUp WelGlass

Specification	Description			
Product family	BY200P L-B	BY200P B-W		
System power	27W/15W	27W/15W		
System output	2600lm/1400lm	2600lm/1400lm		
System efficiency	>95lm/W			
ССТ	NW (4000K) CW (6500K)			
CRI	85			
SDCM	SDCM<5			
Optical	Lambertian (PC)	Batwing (Glass)		
IP rating	IP65/ IK08			
Classification	Class I			
	Body: High-quality die-cast aluminum			
Materials	Body Coating: Corrosion Proof WF2			
	Cover: Heat Resistance Glass/PC			
Lifetime	50000 hrs (LM70)			
Color	Grey			
Dimension	D215xW218xH205 (in mm)	D215xW218xH174 (in mm)		
Weight	2.2 kg	2.4 kg		
Driver	Fixed Output			
Input Voltage	220-240V、50/60 Hz			
Power factor	> 0.95			
Та	-30°C – +50°C			
Mounting	Pipe/Bracket			
Optional Accessories	Bracket - BY200ZMB WireGuard - BY200ZWG			



April 2014 Data subject to change

Ordering information

Basic Unit

Description	12NC	Rated System Power (W)	ССТ	Beam	Cover
BY200P LED25 B-W/NW PSU	911401578611	27W	4000K	B-W	GLASS
BY200P LED25 B-W/CW PSU	911401578711	27W	6500K	B-W	GLASS
BY200P LED12 B-W/NW PSU	911401579511	15W	4000K	B-W	GLASS
BY200P LED12 B-W/CW PSU	911401579211	15W	6500K	B-W	GLASS
BY200P LED25 L-B/NW PSU	911401579011	27W	4000K	L-B	PC
BY200P LED25 L-B/CW PSU	911401578811	27W	6500K	L-B	PC
BY200P LED12 L-B/NW PSU	911401579311	15W	4000K	L-B	PC
BY200P LED12 L-B/CW PSU	911401579411	15W	6500K	L-B	PC

Accessories

Description	12NC	
BY200Z MB	911401578911	Mounting Bracket for BY200P
BY200Z WG	911401579111	Wire Guard for BY200P



© 2012 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.