

Trade Luminaires Portfolio

Philips Lighting Vietnam
2019

PHILIPS

TBS068



PHILIPS

Datasheet

Product Family		TBS068 2ft	TBS068 4ft
Optical	Light source	NA	
	Lumen output	NA	
	CCT	NA	
	CRI	NA	
	SDCM	NA	
	Photometric	NA	
Electrical	Input Voltage	220-240V;50/60Hz	
	LED tube Wattage	Max.10W	Max.20W
	Power Factor	NA	
	Surge Protection	NA	
	Flicker	NA	
	Control	NA	
System Efficiency		NA	
Life time		1 year Warranty (without LED tube)	
Operating temperature		Ta: 25°C	
IP		IP20	
IK		NA	
Application metrix		Office	
Louver&Optics		G2,M2*	
Installation		Recessed	
Dimension		3XTLED:597mmx597mmx75mm 4XTLED:597mmx597mmx75mm	2XTLED:1197mmx297mmx75mm 3XTLED:1197mmx597mmx75mm
Package information		2in1 industry package	
Class		Class I	
Certificate&Approbation		NA	
EMC&EMI&Harmonic		EMC&EMI&Harmonic performance depends on LED tubes performance, if customer have relevant requirements, please consult Philips distributor.	

*G2=pre-anodized specular aluminium,
M2= pre-anodized matt aluminium

911401500351TBS068 2xTLED W30L120 M2
 911401501651TBS068 3xTLED W60L120 M2
 911401500451TBS068 3xTLED W60L60 M2
 911401501551TBS068 4xTLED W60L60 M2
 911401500551TBS068 2xTLED W30L120 G2
 911401501451TBS068 3xTLED W60L120 G2
 911401500651TBS068 3xTLED W60L60 G2
 911401501751TBS068 4xTLED W60L60 G2